



Quality Products. Service Excellence.

Linear Amplifier *HL-700 Series*

(Circa 1960-1970 - No longer in production)

Features



- BAND COVERAGE
 - 75 Meter, 40 Meter, 20 Meter, 15 Meter & 10 Meter Amateur Bands
- TUBE COMPLIMENT
 - Choice of either (4) 811A Triodes or (4) 572-B Triodes
 - Operated AB2 - Grounded Grid Service
- MODE AND DUTY CYCLE
 - SSB (700 Watts Input) - dependant on supply voltage.
 - CW (700 Watts Input) - dependant on supply voltage.
- DRIVE POWER
 - 75-100 Watts
- COOLING
 - Forced Air
- ALC
 - None
- TUNING
 - Vernier tuning
 - 0 - 100 dial skirt log for easy resetting
- INPUT CIRCUIT
 - Untuned
- OUTPUT CIRCUIT
 - Pi-Network
- ANTENNA RELAY
 - None (supplied externally) - amplifier is designed to follow an exciter
- METERING
 - (4) Simpson Meters
 - High Voltage, Grid Current, Plate Current & Relative Output
- FINISH
 - Smooth Grey Baked Enamel

Data subject to change without notice

© 2024. Hammond Manufacturing Ltd. All rights reserved.