Toroidal Straight Isolation - Plug In (178 & 240 Series)

Toroidal Isolation Plug In (120V to 120V)

- Primary 120VAC, 50/60 Hz., Secondary 120VAC.
- · Provides circuit isolation.
- Toroidal transformer for high isolation, low noise, light weight, cool operation and low profile.
- World wide applications, 50 or 60 Hz. operation, step down (120VAC to 120 VAC).
- · Standard 3-wire, grounded plug (for use with adaptors for proper grounding).
- Input (primary) connected to a 5 foot long cord & standard North American plug (NEMA 5-15P).
- Output (secondary) connected to two standard 3 wire grounded receptacles (NEMA 5-15R).
- · Features include ventilated black steel case, rocker lighted on-off switch & circuit breaker protected output.
- · North American Mark of Safety C UL & UL listed (File #E211544).
- Remember These units do NOT convert line frequency.



Toroidal Isolation Plug In (240V to 240V)

- Primary 240VAC, 50/60 Hz., Secondary 240VAC.
- Provides circuit isolation.
- · Toroidal transformer for high isolation, low noise, light weight, cool operation and low profile.
- · World wide applications, 50 or 60 Hz. operation, step down (240VAC to 240VAC).
- · Standard 3-wire, grounded plug (for use with adaptors for proper grounding).
- Input (primary) connected to a 5 foot long cord & standard North American plug (NEMA 6-15P).
- Output (secondary) connected to a standard 3 wire grounded duplex receptacle (NEMA 6-15R).
- · Features include ventilated black steel case, rocker lighted on-off switch & circuit breaker protected output.
- North American Mark of Safety C UL & UL listed (File #E211544).
- Remember These units do NOT convert line frequency.



EUROPE Basingstoke, UK 01256 812812

AUSTRALIA Queenstown, Australia 61-8-8240-2244



	Part No.	Capacity VA	# of Outlets	Dimensions (Inches)		
				Length	Width	Height
	178CT	250	2	8.25	6.00	4.00
	178DT	500	2	9.00	6.00	4.00
	178ET	750	2	10.25	7.50	5.00
	178FT	1000	2	10.25	7.50	5.00
	178GT	1500	2	12.50	9.00	5.00



	Part No.	Capacity	# of Outlets	Dimensions (Inches)			
	Fart No.	VA		Length	Width	Height	
ſ	240CT	250	2	8.25	6.00	4.00	
	240DT	500	2	9.00	6.00	4.00	
	240ET	750	2	10.25	7.50	5.00	
ſ	240FT	1000	2	10.25	7.50	5.00	
	240GT	1500	2	12.50	9.00	5.00	





Cheektowaga, NY (716) 630-7030

www.hammondmfg.com

ຊີ **59** ຊົ