

# 1591T



## Translucent Polycarbonate



### Key Features

- Ideally suited for mounting printed circuit boards.
- Perfect for applications where parts, sensors or indicators need to be visible.
- Ice Blue version is almost totally transparent to blue, white and near white LEDs, readouts & displays.
- Crystal Clear version is almost totally transparent.
- IR Red version is almost totally transparent to infrared devices.
- Integral card guides accept 1.5 mm (0.062") P.C. cards.
- Lap joint construction provides protection against access of dust and splashing water.
- Designed to meet IP54.
- Molded from flame retardant, easy to machine, translucent polycarbonate (material carries a UL flammability rating of 94V-0).
- Lid is secured with M3 x 10 mm Philips machine screws, threaded into integral brass bushings.

Part Number	Color	Units	Length	Width	Enclosure Depth (Less Lid)
1591ATBU	Ice Blue	Inches mm	3.9 100	2 50	0.8 21
1591ATCL	Clear				
1591ATRD	IR Red				
1591STBU	Ice Blue	Inches mm	4.3 110	3.2 82	1.6 40
1591STCL	Clear				
1591STRD	IR Red				
1591BTBU	Ice Blue	Inches mm	4.4 112	2.4 62	1.1 27
1591BTCL	Clear				
1591BTRD	IR Red				
1591CTBU	Ice Blue	Inches mm	4.7 120	2.6 65	1.4 36
1591CTCL	Clear				
1591CTRD	IR Red				
1591DTBU	Ice Blue	Inches mm	5.9 150	3.2 80	1.8 46
1591DTCL	Clear				
1591DTRD	IR Red				
1591ETBU	Ice Blue	Inches mm	7.5 191	4.3 110	2.2 57
1591ETCL	Clear				
1591ETRD	IR Red				

