1591R



Multipurpose - EMI/ RFI Coated

Key Features:

- Ideally suited for vertical mounting of printed circuit boards; internal side walls include molded in card guides.
- Molded from flame retardant ABS plastic (material carries a UL flammability rating of 94V-0).
- Interior of each enclosure part is specially masked and sprayed with an RFI/EMI copper conductive coating (see photo above).
- Coating manufacturer specifies an attenuation of more than 75 db from 1 Mhz. to 1 Ghz.
- Designed to meet IP54.
- Lid is secured with M3 x 10 mm Philips machine screws, threaded into integral brass bushings. Perfect for applications when repetitive assembly and disassembly are required.
- Smooth black finish with black screws.

For general purpose applications where shielding is not required, try series "1591" on page 16

Critical Data, No Questions

PDF Data Sheets, 2D AutoCAD, and 3D Models are available for download immediately from our web site.



www.hammondmfg.com USA (716) 630-7030

Canada 030 (519) 822-2960

Quebec 2960 (450) 975-1884 Europe (UK) Australia 01256 812812 +61-8-8240-2244

49



Hand Held- EMI / RFI Coated

Accessories

Flange Kits (see table)

Belt Clip Kits

100-pack of replacement screws





1599CLIP



1591MS100BK (black)

Part Number	Color	Units	Length	Width	Enclosure Depth Less Lid	Flange Kit
1591RLBK	Black	Inches mm	3.3 85	2.2 56	1.4 35	1591FLBK
1591RABK	Black	Inches mm	3.9 100	2 50	0.8 21	1591FABK
1591RSBK	Black	Inches mm	4.3 110	3.2 82	1.6 40	1591FSBK
1591RBBK	Black	Inches mm	4.4 112	2.4 62	1.1 27	1591FBBK
1591RCBK	Black	Inches mm	4.7 120	2.6 65	1.4 36	1591FCBK
1591RTBK	Black	Inches mm	4.7 120	3.2 80	2.2 55	1591FTBK
1591RUBK	Black	Inches mm	4.7 120	4.7 120	2.2 55	1591FUBK
1591RVBK	Black	Inches mm	4.7 120	4.7 120	3.5 90	1591FUBK
1591RGBK	Black	Inches mm	4.8 121	3.7 94	1.2 30	1591FGBK
1591RDBK	Black	Inches mm	5.9 150	3.2 80	1.8 46	1591FDBK
1591RHBK	Black	Inches mm	6.5 165	2.8 71	1 25	1591FHBK
1591REBK	Black	Inches mm	7.5 191	4.3 110	2.2 57	1591FEBK



Canada (716) 630-7030 (519) 822-2960

Quebec (450) 975-1884

Europe (UK) Australia 01256 812812 +61-8-8240-2244

50